

**1. Identification of the product and company**

Product name:

FLOORCOAT SOLID 15-25-40

Supplier:

Date: 28-01-2011

Floorcoat A/S

Replace

Egestubben 4C

DK-5270 Odense N

Telephone: 004566180306

Fax: 004566184346

2. Composition/Information on Ingredients:

Content:

CAS-nr:	EU:	%:	Chemical name	Class.:	R-phrases
111-90-0	203-917-7	> 30% < 5%	aromatic polyurethane dispersion ethyldiglycol	Xi	R 36

3. Hazards identification:**Main hazards for man and environment:***May cause eye irritation.***Symptoms:****4. First aid measures:****General:****Inhalation:***Remove victim to fresh air, and keep under surveillance. Seek medical attention if irritation persists.***Eye Contact:***Any contact lenses are removed. Immediately flush with plenty of water for at least 15 min. Eyelids widely open.***Skin Contact:***Remove contaminated clothing. Wash off skin with soap and plenty of water. Skin cleaner can be used, defatted skin lubricated with a moisturising cream.***Ingestion:***Rinse mouth and then drink plenty of water. DO NOT INDUCE VOMITING. If vomiting occurs, keep head high so that no stomach contents get into the lungs. Seek medical help.***Combustion:****5. Fire fighting measures:****Extinguishing media:***Not combustible. Use extinguishing media appropriate for surrounding fire.***Extinguishing media which must not be used:****Special hazards:***Product is not flammable, but if it is involved in a burn, may develop harmful smoke.***Protective equipment****General**



6. Accidental Release measures:

Personal precautions:

Wear skin, eye and respiratory protection during cleanup

Environmental precautions:

Methods for cleaning:

Soak up material with absorbent and shovel into a chemical waste container. Afterwards wash with water and soap.

General:

7. Handling and storage:

Handling:

Prevent skin and eye contact. Avoid breathing vapours/aerosols.

Storage:

Store cool and dry in original packing.

8. Personal protection/Exposure controls:

Respiratory protection:

If needed, use certified respirator for organic vapours

Skin protection:

Wear gloves of vinyl, latex, neoprene

Eye protection:

Wear chemical tight goggles.

Exposure controls

CAS-nr:

111-90-0

Chemical name

ethylidiglycol

LV

Rem.:

9. Physical and chemical properties:

Appearance

Liquid

Colour:

White translucent

Odour:

mild amine

Flash point:

Flammability:

Solubility:

Soluble in water

10. Stability and reactivity:

Stability:

Stable under normal conditions

Conditions to avoid:

11. Toxicological information:

Inhaling:

Prolonged inhalation may cause headache and nausea.

Skin contact:

Organic solvents, degreasing the skin. Organic solvents can be absorbed through the skin.

Repeated and long term contact with the product may cause redness and irritation.

Eyes:

Splashes in the eye may cause irritation.

Ingestion:

Ingestion irritates the mucous membranes of the mouth, throat and stomach.

Long term exposure:

Inhalation of high concentrations or frequent inhalation of even small amounts of organic solvents may cause damage to liver, kidneys and central nervous system.

12. Ecological considerations:

Ecotoxicity:

Products must not enter drains or watercourses.

Mobility:



Ability

Accumulation:

General:

Other relating data:

13. Disposal considerations:

Dispose in accordance with local and state regulations

14. Transport information:

Product is not covered by regulations on transport of dangerous substances.

15. Regulatory information

Classification:

Restrictions by using:

Not for use by people under 18 years.

Special training requirements:

The user must be familiar with these MSDS.

16. Other information: